

Spatial Variation of Wind Stress and Wave Field in the Shoaling Zone

Timothy L. Crawford
U.S. Dept. Commerce / NOAA
Air Resources Laboratory Field Research Division
1750 Foote Drive
Idaho Falls, ID 83402
phone: (208) 526-9513 fax: (208) 526-2549 email: Tim.Crawford@noaa.gov

Gennaro H. Crescenti
U.S. Dept. Commerce / NOAA
Air Resources Laboratory Field Research Division
1750 Foote Drive
Idaho Falls, ID 83402
phone: (208) 526-2328 fax: (208) 526-2549 email: Jerry.Crescenti@noaa.gov

Document Number: N00014-97-F-0123
<http://www.noaa.inel.gov/frd/Projects/shoal.html/>

LONG-TERM GOALS

Existing atmospheric models for predicting surface stress and turbulent structure in the shoaling zone fail because of their inability to properly account for wave age, shoaling, and internal boundary layer development. Accurate model simulation of the surface stress and turbulence above the air-sea interface is important for a number of applications including understanding wave growth and decay. Under this ONR Advance Research Initiative, our goals are:

1. to measure the spatial variation of the wind, surface stress and ocean wave fields in the shoaling zone and to provide quality-controlled data to the shoaling community; and
2. to study the relationship between the spatial varying mean wind, stress, turbulence structures, and surface wave fields in order to model effects of wave age, shoaling, and internal boundary layer development on the drag coefficient and momentum transfer.

OBJECTIVES

The key to achieving our goals is the development of a data archive containing simultaneous observations of the spatially varying wave, wind, and stress fields in the shoaling zone. At the start of this project, instrument systems for making such observations did not exist. This year, we completed our first objective which was to develop and demonstrate an efficient measurement system. This report focuses on instrument system development and its application in a pilot study.

APPROACH

The LongEZ (N3R) research aircraft (<http://www.noaa.inel.gov/frd/Capabilities/LongEZ/>) is well known for its high fidelity observations of mean meteorological parameters and mass, momentum, and energy flux in marine boundary layers (Fig. 1). However, missing was the ability to measure wave

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 SEP 1999		2. REPORT TYPE		3. DATES COVERED 00-00-1999 to 00-00-1999	
4. TITLE AND SUBTITLE Spatial Variation of Wind Stress and Wave Field in the Shoaling Zone				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Dept. Commerce /National Oceanic and Atmospheric Administration (NOAA),Air Resources Laboratory Field Research Division,1750 Foote Drive,Idaho Falls,ID,83402				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 5	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

height, roughness, phase speed, and directional spectra. To supplement these measurements, a pod was added below the aircraft containing a Ka-band radar and laser altimeter array. These new sensors were integrated into the data system and processing software. With such a novel airborne system, we could, for the first time, freely explore the spatially developing wind field, surface stress, and wave field within the shoaling zone.



Figure 1. LongEZ N3R at 10 m above the sea surface during the SHOWEX pilot study.

WORK COMPLETED

In preparation for the spring pilot study, all instruments were calibrated and installed on N3R. During March 1999, 23 missions covering 75 flight hours were flown under various atmospheric and wave field conditions at the U. S. Army Field Research Facility (FRF) located in Duck, North Carolina. Post field study calibrations were completed and applied to data acquired. Flight scenarios included parallel and perpendicular runs at various altitudes with respect to the coastline as well as numerous slant and spiral soundings. N3R also acquired meteorological information on the boundary layer structures over the nearby Albermarle and Currituck Sounds. Several flights were flown over Lake Mattamuskeet in an attempt to further understand internal boundary layer development. All data were made available to collaborating scientists in netCDF format on CD-ROM.

During September and October, final preparations were completed to N3R for the participation in the Shoaling Wave Experiment (SHOWEX) experiment. Major work focused on flight tests to insure instrumentation and the data system were functioning correctly. Flight maneuvers included pitch and yaw calibrations. Wind circles and boxes were included to verify the proper measurement of the wind. Low-level legs were also included over Mud Lake near Terreton, Idaho to verify the proper operation of the laser altimeter array and the Ka-band radar (scatterometer). In addition, the data acquisition and post-processing software that are to be used for these experiments were updated to provide a more robust system than in previous field campaigns.

We are also cooperating with Dr. Ken Melville of the Scripps Institute of Oceanography (SIO) to develop a new Wave Breaking and Dissipation measurement system for the November SHOWEX field study. The Modular Aerial Sensing System (MASS) will measure the kinematics and dynamics of breaking waves in the transition zone between deepwater breaking and depth-limited breaking on the continental shelf. MASS will allow the geometry, kinematics, and statistics of breaking leading to whitecaps to be measured using video imagery from the LongEZ. Image sequence analysis will be used to determine $L(c)dc$, the length per unit area of breaking crests in the velocity range $(c, c+dc)$. SIO will correlate this fundamental statistical distribution function and its moments with bottom topography and with wind and wave variables, including the wave directional spectrum. The prototype MASS prototype was initially tested on N3R in November 1997. More information can be found at <http://www-mpl.ucsd.edu/people/melville/MASS.htm/>. Figure 2 shows the instrumentation to be flown during the November 1999 SHOWEX field study. Not shown is the MASS system. The MASS computer system will mount above NOAA's main computer system. The MASS video cameras mount in the tail section of the pod just behind the NASA Ka-band radar.




Figure 2. Identification and location of the various instrument systems on LongEZ N3R.

RESULTS

The SHOWEX spring pilot study was successfully conducted at the U. S. Army Corps of Engineers Field Research Facility (FRF) located in Duck, North Carolina during a three-week period in March 1999. N3R flew 23 missions (75 flight hours) under a variety of atmospheric and wave field conditions. High fidelity turbulence flux measurements have been acquired by N3R during the SHOWEX spring pilot study. These measurements included the mean and turbulent wind field, heat flux, and moisture flux. The Ka-band radar, designed by Doug Vandemark of NASA, has demonstrated the ability to measure the mean square slope of ocean waves with a footprint one meter

in size. The array of three laser altimeters has been used to observe the characteristics of the larger waves. The data from this pilot study was quality controlled and is available as netCDF files via CD-ROM or FTP. Collaborating scientists are currently analyzing these data. Publications are listed below.

IMPACT/APPLICATIONS

Our laser array approach has proved successful and is being adapted by others. Dr. Mark Donelan has adopted the laser approach for wave measurement from a ship. NASA, recognizing the power of the airborne laser wave measurements, funded the Wave Profile Experiment (WAPEX) to reduce the uncertainty in the electromagnetic range bias that corrupts satellite sea surface topography measurements (<http://www.noaa.inel.gov/frd/Projects/wapex.html>). N3R laser measurements are being used to refine EM bias models for large-scale tilt, short-scale diffraction, and hydrodynamic effects.

TRANSITIONS

The pilot study data archive is being analyzed in detail by Jielun Sun and Larry Mahrt. We are also advising Mark Donelan on the development of wave measurement system for shipboard use.

RELATED PROJECTS

Although funded separately, this project is a cooperative effort with Doug Vandemark (NASA, Ka-band radar development and analysis, N00014-97-F-0179), Jielun Sun (NCAR, data interpretation, N00014-98-1-0245), and Larry Mahrt (Oregon State University, data interpretation, N00014-97-1-0279).

PUBLICATIONS

Crescenti, G. H., T. L. Crawford, and E. J. Dumas, 1999: Data report: LongEZ (N3R) participation in the 1999 Shoaling Waves Experiment (SHOWEX) spring pilot study. NOAA Tech. Memo., ERL ARL-232, Silver Spring, MD, 86 pp.

Dobosy, R. J., T. L. Crawford, D. Vandemark, and C. A. Vogel, 1999: Measurement of ocean surface in shoaling zones by laser array and Ka-band radar. *Fourth International Airborne Remote Sensing Conference and Exhibition*, ERIM International, 21-24 June, Ottawa.

Mahrt, L., D. Vickers, J. Sun, T. Crawford, C. Vogel, and E. Dumas, 1999: Coastal zone boundary layers. Preprint, *13th Symposium on Boundary Layers and Turbulence*, Dallas, TX, Amer. Meteor. Soc., 403-406.

Sun, J., L. Mahrt, D. Vickers, J. Wong, T. Crawford, C. Vogel, E. Dumas, P. Mourad, and D. Vandemark, 1999: Air-sea interaction in the coastal shoaling zone. Preprint, *13th Symposium on Boundary Layers and Turbulence*, Dallas, TX, Amer. Meteor. Soc., 343-345.

Vandemark, D., T. Crawford, R. Dobosy, T. Elfouhaily, and B. Chapron, 1999: Sea surface slope statistics from a low-altitude aircraft. *IEEE Proceedings of International Geoscience and Remote Sensing Symposium (IGARSS)*, Hamburg, 28 June - 2 July.

- Vandemark, D., P. Mourad, T. Crawford, C. Vogel, and J. Sun, 1999: Measured correlations between roll-vortex signatures and radar-inferred sea surface roughness. *IEEE Proceedings of International Geoscience and Remote Sensing Symposium (IGARSS)*, Hamburg, 28 June - 2 July.
- Vandemark, D., P. D. Mourad, T. L. Crawford, C. A. Vogel, J. Sun, S. A. Bailey, and B. Chapron, 1999: Measured changes in ocean surface roughness due to atmospheric boundary layer rolls. *J. Geophys. Res.*, submitted.
- Vogel, C. A., T. L. Crawford, J. Sun, and L. Mahrt, 1999: Spatial variation of the atmospheric surface drag coefficient within a coastal shoaling zone. Preprint, *13th Symposium on Boundary Layers and Turbulence*, Dallas, TX, Amer. Meteor. Soc., 347-348.